

Medallion Series



Quality Commercial Cooking Equipment

HD11-1HT-0, HD11-1HT-M

11" WIDE EVEN HEAT HOT TOP RANGE
attachment with storage base, or as modular top

Standard Features

- Stainless steel front and sides STANDARD
- 6" (152mm) chrome steel adjustable legs
- Adjustable stainless steel front rail 6-1/16" (154mm) to 7-5/8" (194mm)
- One (1), 30,000 BTU (8.8 kW), "H-Type" Cast-Iron Burner, per Extra Heavy 11" W, 7/8" (thick) top section
- Automatic Single Standing Pilot ignition.
- 1-1/4" NPT front manifold.
- Storage base interior is aluminized steel.
- One year limited parts & labor warranty, (USA and Canada only)

Optional Features


- Stainless steel back rear panel
- Stainless steel common front rail up to 68" (1728mm) wide, (No additional charge)
- Rear gas connection on select models, 3/4 or 1" NPT
- End caps and cover (no charge)- Must specify
- Polyurethane non-marking swivel casters (2) w/front brakes.
- Storage base shelf-aluminized or stainless steel
- Single deck stainless steel high shelf
- 10" (254 mm), 17" (432mm) 22.375" (568mm) 34.375" (873mm) high stainless steel backguard



Short Form Specifications:

Heavy-Duty "Medallion Series" gas 11" Hot Top attachment with storage base, Model : HD11-HT-0 manufactured by American Range. Storage Base with removable hinged door. To have stainless steel front and sides with 6" chrome legs (unless otherwise specified). One (1) 11" wide x 7/8" thick even heat heavy duty hot top totaling 30,000 Btu/hr. Unit to be 11-3/8" (288mm) wide and 38" (965mm) deep with front rail fully extended. Adjustable front rail maximum of 7-5/8" (194mm). Specify Natural gas (NG) or Liquid Propane gas (LP). UL, CUL, NSF, MEA listed. (also available as a Modular Top-Model: HD11-HT-M).

11" WIDE EVEN HOT TOP RANGE attachment with storage base,
or as modular top



Exterior Dimensions

Model #	HD11-1HT-0	HD11-1HT-M
Width	11-1/4"/285mm	11-1/4"/285mm
Depth	38"/965mm (Rail out Dim)	38"/965mm
Height w/NSF legs	36"/914mm	36"/914mm(w/stand)
Height Less NSF Legs	30"/762mm	6-7/8"/175mm (less stand)

Storage Base Interior

Width	6-3/4"/171mm	N/A
Depth	30"/762mm	N/A
Height	20"/508mm	N/A
Unit Weight (LB/KG)	185/84	110/50

INPUT-Btu/hr (N-Gas)	HDT11-1HT-0	KW Eq	HD11-1HT-M	kW Equivalent
Hot Top Burner	30,000	8.79	30,000	8.79
(30,000BTUea)	30,000	8.79	30,000	8.79
TOTAL				

0= Storage Base M= Modular Top

Installation Notes:

Combustible Wall Clearances

Sides: 6" (152mm)

Back: 6" (152mm)

For reduced clearances, refer to ANSI Z223.1/NFPA #54 and CAN/CGA B149.

Entry Clearance:

Crated: 16-1/4" (413mm)

Uncrated: 11-7/8" (302mm)

Manifold Pressure:

Natural 6 W.C. (15 mbar)

Propane 10 W.C. (25 mbar)

NOTE: Data applies only to North America.

Gas Input Ratings shown here are for installations up to 2,000 ft. (610m) above sea level. Specify altitudes over 2,000 ft.

Gas Input Ratings shown here are for installations up to 2,000 ft. (610m) above sea level. Specify altitudes over 2,000 ft.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

Please specify gas type when ordering.



Because of continuing product improvement these specifications are subject to change without notice.